

POWDERS FOR ADVANCED CERAMICS

Number Issue

PD-4012 2-20.05.2016

BORON CARBIDE GRADE HP, GRADE HS

Chemical Formula B₄C

Chemical Name Boron Carbide

HS Number 28499010

Grades Available Product Designation

B₄C Grade HP B₄C Grade HS

Chemical Characteristics

(Mass fraction in % [cg/g]; ppm [µg/g])


	Grade HP		Grade HS				
B:C Ratio	3.8 -	3.9		3.7	-	3.8	
C	min.	21.8		min.		21.8	
N	max.	0.7	%	max.		0.7	%
O	max.	1.0		max.		1.7	
Fe	max.	0.05		max.		0.05	
Si	max.	0.15		max.		0.15	
Al	max.	0.05		max.		0.05	
Other ¹⁾	max.	0.5	%	max.		0.5	%
Physical Characteristics							
Specific Surface Area ²⁾	6.0 -	9.0	m²/g	15.0	-	20.0	m²/g
Green Density ³⁾	1.5 -	1.7	g/cm ³	1.6	-	1.8	g/cm ³
Particle Size Distribution ⁴⁾							
D 90 %	4.5 -	7.5	μm	2.0	-	4.0	μm
D 50 %	1.5 -	3.5	μm	0.6	-	1.2	μm
D 10 %	0.3 -	0.6	μm	0.1	-	0.3	μm

¹⁾ Sum total Ca, Cr, Mg, Mn, Ni, Ti, W, 2) TriStar 3-point by BET per ASTM D 3663, 3) 10³ kg/cm², 4) MASTERSIZER by Laser Light Diffraction per ASTM B 822, deglomeration with high energy ultrasonic before analysis

Höganäs **#**

Number PD-4012 Issue 2-20.05.2016

SEM Photomicrograph⁵⁾ scale see photograph, B₄C Grade HS



Packaging 25 kg steel drums with polyethylene inlet.(60 Liter) 8 drums

on one pallet CP1 (1000x1200 mm) = 1 Packaging-unit of 200 kg.

Other packaging/quantity on request.

Lot Size

Höganäs boron carbide powders are available in homogeneous

lots up to 5 tons.

Storage and Handling Storage and handling are subject to the rules and regulations in the country of

use. Store in a closed container.

Hazards identification in Advertising (REGULATION (EC) No 1272/2008)

None.

Documentation An inspection document in accordance with EN 10204 is supplied with every

shipment.

Höganäs Germany GmbH

Im Schleeke 78-91 38642 Goslar/Germany Säckinger Straße 51 79725 Laufenburg/Germany

Phone +49 5321 751-53753

https://www.hoganas.com/en/contact/

The conditions of your use and application of our products, technical assistance and information (whether verbal, written or by way of production evaluations), including any suggested formulations and recommendations, are beyond our control. Therefore, it is imperative that you test our products, technical assistance and information to determine to your own satisfaction whether they are suitable for your intended uses and applications. This application-specific analysis at least must include testing to determine suitability from a technical as well as health, safety, and environmental standpoint. Such testing has not necessarily been done by Höganäs Germany GmbH. All information is given without warranty or guarantee. It is expressly understood and agreed that the customer assumes and hereby expressly releases Höganäs Germany GmbH from all liability, in tort, contract or otherwise, incurred in connection with the use of our products, technical assistance and information. Any statement or recommendation not contained herein is unauthorized and shall not bind Höganäs Germany GmbH. Nothing herein shall be construed as a recommendation to use any product in conflict with patents covering any material or its use. No license is implied or in fact granted under the claims of any patent. In case of order please refer to issue number of the respective product data sheet. All deliveries are based on the latest issue of the product data sheet and the latest version of our General Conditions of Sale and Delivery.